

## UNIVERSAL GRINDING G. RASTELLI R7A

---



### Short description

---

CENTER HEIGHT 165 MM  
DISTANCE BETWEEN TIPS 1000 MM  
GRINDING WHEEL: DIAMETER 400 MM  
STRIP 50 MM  
FORO 127 MM  
RPM 1400 RPM.  
MOVING WITH BATHING  
AUTO INCREMENT  
INCREASE PLONGÉ PLUMBING  
P. the HEAD PIECE 4 SPEED  
THE SPEED RANGE FROM 50 TO 490 G/MIN.  
VARIABLE TILT ANGLE FROM 0 TO 90 DEGREES  
SPINDLE TAPER MK 4  
CONE TAILSTOCK MK 3  
TABLE INCLINATION MAX 4/9 DEGREES

### **GE-TRA-PACK SRL can guarantee its customers the following activities:**

- Disassembly and reassembly of complete companies, with the help of qualified personnel.
- Transportation with own trucks and crane trucks (up to 200 tons).
- Complete revision of machine tools and industrial plants.
- Forklift rental with or without operator.

ROTATION SPEED OF TABLE FROM 0 TO 6 M/MIN.  
ENGINE, HEAD, DOOR OF THE GRINDING WHEEL 4 KW  
ENGINE, HEAD, DOOR, PCS 0,60 KW  
WEIGHT 2000 KG

---

**GE-TRA-PACK SRL can guarantee its customers the following activities:**

- Disassembly and reassembly of complete companies, with the help of qualified personnel.
- Transportation with own trucks and crane trucks (up to 200 tons).
- Complete revision of machine tools and industrial plants.
- Forklift rental with or without operator.